









Fruit Digester come with intermediate shaft for long operational life of parts, easy alignment and easy maintenance.

- 1. Capacity: 3,500 litres to 6,500 litres
- 2. Perforated stainless steel bottom plate
- 3. Intermediate connecting shaft for easy installation and maintenance.
- 4. Thrust bearing provided on intermediate shaft and square shaft.

SHELL & DRIVE



DRIVE

- Electric Motor 30hp to 60hp
- Fluid Coupling
- Speed Reducer: SEW, Flender Hansen, Elecon.

CONNECTING SHAFT

- Flexible Top Coupling.
- Ball Thrust Bearing 51320.
- Intermediate connecting shaft.
- 110mm to 130mm ASSAB 705/709 material.
- Fixed bottom coupling

DIGESTER SHELL

- 114 SQ. or 125 SQ. M.S./ASSAB 705 Shaft c/w SS304 lining.
- 4 pairs or 5 pairs beater arms
- 1 pair bottom expeller arms

For further information, please contact sales office, or:



Excelmech Engineering Sdn. Bhd. (Company No. 862039-X)

Lot 2828, Jln Kelkati 32/168, Off Jln. Sri Gambut Bukit Naga, Seksyen 32, 40460 Shah Alam, Selangor Darul Ehsan, Malaysia Tel: 603-5167 1589 Fax: 603-5167 2588 E-mail: contact@excelmech.com.my

